

HDF3010 SERIES

DC FAN

Operating Temp. Range : 0 - +60 .
 Locked Rotor & Polarity Protected
 Bearing : Ball Bearing
 Housing : Plastic
 Fan Blade : Plastic



30 x 30 x 10 mm

| Type | Mdel | Rated Voltage VDC | Operate Voltage VDC | Rated Current mA | Rated Input W | Rated Speed rpm | Max Air flow m ³ /min | CFM | Max Static Pressure mmAq | inchAq | Noise Level dB(A)/m | Weight gr |
|--------------|-----------------|-------------------|---------------------|------------------|---------------|-----------------|----------------------------------|-----|--------------------------|--------|---------------------|-----------|
| Medium Speed | * HDF3010L-05MB | 5 | 4.5 - 5.5 | 73 | 0.37 | 4900 | 0.06 | 2.1 | 1.1 | 0.04 | 9 | |
| | * HDF3010L-12MB | 12 | 10.8 - 13.2 | 67 | 0.80 | 7100 | 0.09 | 3.2 | 2.3 | 0.09 | 19 | 8 |
| High Speed | * HDF3010L-05HB | 5 | 4.5 - 5.5 | 89 | 0.45 | 5800 | 0.07 | 2.5 | 1.5 | 0.06 | 13 | |

* Approvals = UL / CLR (UL FOR CANADA) / TUV

