

HDF3020 SERIES

DC FAN

Operating Temp. Range : -20 - +60

Locked Rotor & Polarity Protected

Bearing : Ball Bearing

Housing : Plastic

Fan Blade : Plastic



30 x 30 x 20 mm

| Type | Mdel | Rated Voltage VDC | Operate Voltage VDC | Rated Current mA | Rated Input W | Rated Speed rpm | Max Airflow m ³ /min | CFM | Max Static Pressure mmAq | inchAq | Noise Level dB(A)/m | Weight gr |
|--------------|------------------|-------------------|---------------------|------------------|---------------|-----------------|---------------------------------|-----|--------------------------|--------|---------------------|-----------|
| Bottom Speed | * HDF3020L-05LLB | 5 | 4.25 - 5.75 | 70 | 0.35 | 4300 | 0.039 | 1.4 | 1.0 | 0.04 | 19 | |
| Low Speed | * HDF3020L-05LB | 5 | 4.25 - 5.75 | 100 | 0.50 | 5300 | 0.048 | 1.7 | 1.6 | 0.06 | 21 | 29 |
| | * HDF3020L-12LB | 12 | 10.2 - 13.8 | 40 | 0.48 | | | | | | | |
| Middle Speed | * HDF3020L-12MB | 12 | 10.2 - 13.8 | 70 | 0.84 | 7800 | 0.070 | 2.5 | 3.3 | 0.13 | 24 | |

* Approvals = UL / CUR (UL FOR CANADA) / TUV

