



HDF4020 SERIES

DC FAN

Operating Temp. Range : -20 - +60

Locked Rotor & Polarity Protected

Bearing : Ball Bearing

Housing : Plastic

Fan Blade : Plastic



40 x 40 x 20 mm

Type	Model	Rated Voltage VDC	Operating Voltage VDC	Rated Current mA	Rated Input W	Rated Speed rpm	Max Air flow m ³ /min	CFM	Max Static Pressure mmAq	inchAq	Noise Level dB(A) / m	Weight gr
Bottom Speed	* HDF4020L-05LLB	5	4.25 - 5.75	75	0.38	3300	0.10	3.5	1.2	0.05	21	
Low Speed	* HDF4020L-05LB	5	4.25 - 5.75	105	0.53	4200	0.13	4.6	1.8	0.07	23	
	* HDF4020L-12LB	12	10.2 - 13.8	40	0.48							
Middle Speed	* HDF4020L-12MB	12	10.2 - 13.8	70	0.84	5900	0.18	6.4	3.5	0.14	26	
High Speed	* HDF4020L-05HB	5	4.25 - 5.75	230	1.15	7100	0.24	8.5	4.9	0.19	27	27
	* HDF4020L-12HB	12	10.2 - 13.8	95	1.14							
	* HDF4020L-24HB	24	20.4 - 27.6	70	1.68							
Top Speed	* HDF4020L-05HHB	5	4.25 - 5.75	350	1.75	9000	0.31	10.9	8.0	0.31	34	
	* HDF4020L-12HHB	12	10.2 - 13.8	165	1.98							
	* HDF4020L-24HHB	24	20.4 - 27.6	80	1.92							

* Approvals = UL / CUR (UL FOR CANADA) / TUV

-@-@ -@* LL- MSpeed = 5 fan blades / H and HH Speed = 7 fan blades.

