



HDF6025 SERIES

DC FAN

Operating Temp. Range : -20 - +60

Locked Rotor & Polarity Protected

Bearing : Ball Bearing

Housing : Plastic

Fan Blade : Plastic



60 x 60 x 25 mm

| Type | Model | Rated Voltage VDC | Operate Voltage VDC | Rated Current mA | Rated Input W | Rated Speed rpm | Max Air flow m ³ /min. CFM | Max Static Pressure mmAq inchAq | Noise Level dB(A) / m | Weight gr |
|--------------|------------------|-------------------|---------------------|------------------|---------------|-----------------|---------------------------------------|---------------------------------|-----------------------|-----------|
| Low Speed | * HDF6025L-12LB | 12 | 10.2 - 13.8 | 55 | 0.66 | 2550 | 0.30 11 | 1.7 0.06 | 21 | 85 |
| Middle Speed | * HDF6025L-12MB | 12 | 10.2 - 13.8 | 70 | 0.84 | 3000 | 0.36 13 | 2.2 0.09 | 26 | |
| | * HDF6025L-24MB | 24 | 20.4 - 27.6 | 45 | 1.08 | 3200 | 0.39 14 | 2.4 0.09 | 27 | |
| High Speed | * HDF6025L-12HB | 12 | 10.2 - 13.8 | 140 | 1.68 | 4500 | 0.54 19 | 4.9 0.19 | 35 | |
| | * HDF6025L-24HB | 24 | 20.4 - 27.6 | 70 | 1.68 | | | | | |
| Top Speed | * HDF6025L-12HBB | 12 | 10.2 - 13.8 | 220 | 2.64 | 5350 | 0.63 22 | 6.7 0.26 | 41 | |
| | * HDF6025L-24HBB | 24 | 20.4 - 27.6 | 120 | 2.88 | | | | | |

* Approvals = UL / CUR (UL FOR CANADA) / TUV

