



HDF8025 SERIES

DC FAN

Operating Temp. Range : -20 - +60

Locked Rotor & Polarity Protected

Bearing : Ball Bearing

Housing : Plastic

Fan Blade : Plastic



80 x 80 x 25 mm

Type	Model	Rated Voltage VDC	Operate Voltage VDC	Rated Current mA	Rated Input W	Rated Speed rpm	Max Airflow m ³ /min. CFM	Max Static Pressure mmAq inchAq	Noise Level dB(A)/m	Weight gr
Low Speed	* HDF8025L-12LB	12	10.2 - 13.8	65	0.78	1850	0.61 22	1.4 0.06	27	100
Middle Speed	* HDF8025L-12MB	12	10.2 - 13.8	105	1.26	2450	0.81 29	2.4 0.09	32	
	* HDF8025L-24MB	24	20.4 - 27.6	60	1.44	2600	0.86 30	2.7 0.11	33	
High Speed	* HDF8025L-12HB	12	10.2 - 13.8	170	2.04	3150	1.04 37	4.0 0.16	37	
	* HDF8025L-24HB	24	20.4 - 27.6	90	2.16					
Top Speed	HDF8025L-12HMB	12	10.2 - 13.8	250	3.00	3600	1.19 42	5.2 0.20	41	
	HDF8025L-24HMB	24	20.4 - 27.6	110	2.64					

* Approvals = UL / CUR (UL FOR CANADA) / TUV

