


SPECIFICATIONS (Th=32°C)	CODE #	DESCRIPTION
Heat Transfer Cold side	L	Liquid flow cooling
Heat Transfer Warm side	L	Liquid heat removal
Cascade	-	
Cooling Effect	090	90 W at dT=0°C and Th=32°C
Voltage Nominal	24	24 VDC (29,5 VDC MAX)
Current Nominal TE-Module(s)		3,1 A at dT=0°C PE-161-12-15-S (2S)
Fan(s) Cold side	0	None
Fan(s) Warm side	0	None
Thermostat / Regulation & Sensor	0	None
Thermostat Settings Trimmable Accuracy & Hysteresis	0	None
Thermostat Position & Casing	0	None
Options: Protections Rapid Cooling / Economy	0	None None
Weight Overheating Thermostat Max. operating Temperature Enclosed Packing		0,6 kg net 75°C±5°C on warm side heat sink surface 69°C warm side liquid - Individual cardboard box

POS:	ITEM No.:	DESCRIPTION	QTY	NOTE
1	Heat sink	Anodised Alu, silver	1+1	Turbulators inserted
2	Seal	Polyethylene	1	

Qty/Product:	Material:	Project: Standard	
Designed by: Pavel Cech	Approved by / sign.: Hans Lindberg	Customer:	Date/Rev.No: 0-00-02-03
 <p>Supercool AB Box 27, 40120 Göteborg, Sweden tel: +46 31 420530, fax: +46 31 247909 e-mail: pavel@supercool.se www.supercool.se</p>		COOLING-ASSEMBLY	
		LL-090-24-00-00-00	SS-IS02768-1