ET-007-06-11

Peltier cooler module

Data sheet



Imax	[A]	1.5
Vmax	[Vdc]	0.9
Pc max	[W]	0.8
ΔTmax	[°C]	72
A	[mm]	4
A1	[mm]	4
B	[mm]	4
H	[mm]	2.7
L	[mm]	100
Wire	AWG	n/a

- (At hot side temperature Th = 25°C / 298K, under dry N_2)
- Pc max = Cooling power at ΔT = 0 and I = Imax
- ΔTmax = Temperature difference at I = Imax and Pc = 0
- Max hot side temperature Th = 90°C for best long term performance
- Max mounting pressure: 1.5MPa
- Wires: UL-style 1569, 105°C (Unstripped)

Adaptive Thermal Management

Adaptive is a registered trademark of European Thermodynamics Limited.
Web: www.etdyn.com Tel: +44(0)116 279 6899 E-mail: info@etdyn.com

ET-007-06-11

Peltier cooler module

Data sheet - At hot side temperature 25°C









*Note - Waste heat = Heat out of hot side

Adaptive Thermal Management

Adaptive is a registered trademark of European Thermodynamics Limited.

Web: www.etdyn.com Tel: +44(0)116 279 6899 E-mail: info@etdyn.com

ET-007-06-11

Peltier cooler module

Data sheet - At hot side temperature 50°C









*Note - Waste heat = Heat out of hot side

Adaptive Thermal Management

Adaptive is a registered trademark of European Thermodynamics Limited.

Web: www.etdyn.com Tel: +44(0)116 279 6899 E-mail: info@etdyn.com

ET-007-06-11

Peltier cooler module

Data sheet - At hot side temperature 75°C









*Note - Waste heat = Heat out of hot side

Adaptive Thermal Management

Adaptive is a registered trademark of European Thermodynamics Limited.
Web: www.etdyn.com Tel: +44(0)116 279 6899 E-mail: info@etdyn.com